



Product feature

1. PA12、PA6 Nylon tubing has excellence capability to be used high temperature conditions widely.
2. Many kinds of colors to be chosned.
3. Steady size, Little osmotic rate.
4. Be used widely for it's aging resistant, good anti-oil, and high temperature resistant capability.

Specification

Type [Note1]	Tubing OD (mm)	Tubing ID (mm)	Wall Thickness (mm)	Package Length(m)	Working Pressure at 23°C(MPa) [Note2]	Burst pressure at 23°C(MPa)	Bend radius (mm)	Weight per 100M(kg)	Temperature (°C)
PA6040025□□	4.0	2.5	0.75	200	3.5	11.0	30	0.90	-10~70
PA6060040□□	6.0	4.0	1.00	100	3.0	10.0	45	1.80	
PA6080060□□	8.0	6.0	1.00	100	2.0	7.0	65	2.50	
PA6100075□□	10.0	7.5	1.25	100	2.0	7.0	75	3.90	
PA6120090□□	12.0	9.0	1.50	100	2.0	7.0	100	5.70	
PA12040025□□	4.0	2.5	0.75	200	2.5	7.5	25	0.80	-40~70
PA12060040□□	6.0	4.0	1.00	100	2.0	7.0	35	1.60	
PA12080060□□	8.0	6.0	1.00	100	1.5	5.0	55	2.30	
PA12100075□□	10.0	7.5	1.25	100	1.5	5.0	75	3.50	
PA12120090□□	12.0	9.0	1.50	100	1.5	5.0	75	5.10	

[Note1] The first square of "□□" in the type column is for ordering code "unit" and the second is for "color".

[Note2] Working pressure:3 to 1 safety factor.

Relationship of operation pressure and temperature

Temperature	PA6 the percentage of work pressure reached at different temperatures					PA12 the percentage of work pressure reached at different temperatures				
	20°C	40°C	60°C	80°C	100°C	20°C	30°C	50°C	60°C	80°C
Percentage	100%	74%	57%	47%	40%	100%	83%	75%	64%	47%

Ordering code

Pa12 060 040 100M BU				
① Model	② Tubing OD	③ Tubing ID	④ Material length	⑤ Standard color
PA6: Nylon 6 PA12: Nylon 12	040: Φ4.0mm 060: Φ6.0mm 080: Φ8.0mm 100: Φ10.0mm 120: Φ12.0mm	025: Φ2.5mm 040: Φ4.0mm 060: Φ6.0mm 075: Φ7.5mm 090: Φ9.0mm	200M: 200 m/coil(4X2.5) 100M: 100 m/coil(Others)	BU : Blue BK : Black GE : Orange N : Clear WH : White GN : Green R : Red Y : Yellow